




NTN Bearing de Mexico, S.A.



3.543 Inch | 90 Millimeter x 6.299 Inch | 160
Millimeter x 1.575 Inch | 40 Millimeter SKF NU
2218 ECP/C3 Cylindrical Roller Bearings

Bearing No. NU 2218 ECP/C3

NU 2218 ECP/C3 Bearing 2D drawings and 3D CAD
models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.201
EAN	7316577031884
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	90MM Bore; Straight Bore Profile; 160MM Outside Diameter; 40MM Width;



NTN Bearing de Mexico, S.A.

	Polymer Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Int
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 2218 ECP/C3
Weight / LBS	7.05
D	6.299 Inch 160 Millimeter
B	1.575 Inch 40 Millimeter
d	3.543 Inch 90 Millimeter
bore diameter:	90 mm
static load capacity:	315 kN
outside diameter:	160 mm
precision rating:	Not Rated
overall width:	40 mm
maximum rpm:	5000 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Polyamide
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	40 mm
operating temperature range:	Maximum of +300 ° F



NTN Bearing de Mexico, S.A.

fillet radius:	2 mm
dynamic load capacity:	280 kN
series:	NU22