



NTN Bearing de Mexico, S.A.



NU 310 ECM/C3 Bearing 2D drawings and 3D CAD models

1.969 Inch | 50 Millimeter x 4.331 Inch | 110 Millimeter x 1.063 Inch | 27 Millimeter SKF NU 310 ECM/C3 Cylindrical Roller Bearings

Bearing No. NU 310 ECM/C3

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.346
EAN	7316576623882
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	50MM Bore; Straight Bore Profile; 110MM Outside Diameter; 27MM Width;



NTN Bearing de Mexico, S.A.

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inter
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 310 ECM/C3
Weight / LBS	2.964
D	4.331 Inch 110 Millimeter
d	1.969 Inch 50 Millimeter
B	1.063 Inch 27 Millimeter
bore diameter:	50 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	110 mm
maximum rpm:	8000 RPM
overall width:	27 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	27 mm



NTN Bearing de Mexico, S.A.

operating temperature range:	Maximum of +300 ° F
fillet radius:	2 mm
dynamic load capacity:	127 kN
series:	NU3
static load capacity:	112 kN